


Front view



Rear view



Resettable fuse



MCB

Circuit Protection	Code
Fuse	F
MCB	CR



IEC 60309 Inlet

32A model :	Circuit Protection
H12C13-32A/ F _EN/3B- 1	Resettable Fuse x 2
H12C13-32A/ CR _EN/3B- 1	1-pole MCB x 2

Input Rating : 32Amp, 230V
Cordset : 3 meter 4.0mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
Circuit A : Output 16A max., C13 #1-6
Circuit B : Output 16A max., C13 #7-12
Weight : Net 4.63 Kg / Gross 4.88 Kg

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color: Black



Open end

20A model :	Circuit Protection
H12C13-20A/ F _OE/3B- 1	Resettable Fuse x 1
H12C13-20A/ CR _OE/3B- 1	1-pole MCB x 1

Input Rating : 20Amp, 230V
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or 20A hydraulic MCB x 1
Circuit : Output 20A max., C13 #1-12
Weight : Net 3.16 Kg / Gross 3.42 Kg



IEC 60309 Inlet

16A model :	Circuit Protection
H12C13-16A/ F _EN/3B- 1	Resettable Fuse x 1
H12C13-16A/ CR _EN/3B- 1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-12
Weight : Net 3.09 Kg / Gross 3.35 Kg



IEC320 C20

16A model :	Circuit Protection
H12C13-16A/ F _C20/3B- 1	Resettable Fuse x 1
H12C13-16A/ CR _C20/3B- 1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-12
Weight : Net 3.02 Kg / Gross 3.27 Kg



IEC320 C14

10A model :	Circuit Protection
H12C13-10A/ F _C14/3B- 1	Resettable Fuse x 1
H12C13-10A/ CR _C14/3B- 1	1-pole MCB x 1

Input Rating : 10Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 10A resettable fuse or 10A hydraulic MCB x 1
Circuit : Output 10A max., C13 #1-12
Weight : Net 3.00 Kg / Gross 3.26 Kg

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

EMC Compliance : CE / EMC
Safety Compliance : CE / LVD & UKCA
Tested to EN 62368-1:2014 / A11:2017 standard
Tested to EN 60730-1:2016 / A1:2019 standard
Environment Compliance : RoHS3 & REACH