


1-Phase basic specification drawing

230V 16A / 20A / 32A PDU : UK x 4 + C13 x 12 + C19 x 4

unit : mm



Circuit Protection	Code
Fuse	F
MCB	CR



IEC 60309 Inlet

32A model :	Circuit Protection
V4UK135-12C13-4C19-32A- F_EN/3B-1	Resettable Fuse x 2
V4UK135-12C13-4C19-32A- CR_EN/3T-1	1-pole MCB x 2

Input Rating : 32Amp, 230V
Cordset : 3 meter 4.0mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
Circuit A : Output 16A max., C13 #1-6 + UK #13-14 + C19 #C1-C2
Circuit B : Output 16A max., C13 #7-12 + UK #15-16 + C19 #C3-C4
Weight : Net - Kg / Gross - Kg

PDU Feed	Code
Bottom	B
Top	T



Open end

20A model :	Circuit Protection
V4UK135-12C13-4C19-20A- F_OE/3B-1	Resettable Fuse x 1
V4UK135-12C13-4C19-20A- CR_OE/3T-1	1-pole MCB x 1

Input Rating : 20Amp, 230V
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or 20A hydraulic MCB x 1
Circuit : Output 20A max., C13 #1-12 + UK #13-16 + C19 #C1-C4
Weight : Net - Kg / Gross - Kg

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8



IEC 60309 Inlet

16A model :	Circuit Protection
V4UK135-12C13-4C19-16A- F_EN/3B-1	Resettable Fuse x 1
V4UK135-12C13-4C19-16A- CR_EN/3T-1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-12 + UK #13-16 + C19 #C1-C4
Weight : Net - Kg / Gross - Kg



IEC320 C20

16A model :	Circuit Protection
V4UK135-12C13-4C19-16A- F_C20/3B-1	Resettable Fuse x 1
V4UK135-12C13-4C19-16A- CR_C20/3T-1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-12 + UK #13-16 + C19 #C1-C4
Weight : Net - Kg / Gross - Kg

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

EMC Compliance : CE / EMC
Safety Compliance : Tested to EN 62368-1:2014 / A11:2017 standard
Tested to EN 60730-1:2016 / A1:2019 standard
Environment Compliance : RoHS3 & REACH